

Material Safety Data Sheet

Revision Date: 08/16/2007
Z17000000227/Version: 1.1
Print Date: 10/29/2008
Page: 1/8

1. Identification of the substance/preparation and of the company/undertaking

Product name: KODAK RP X-OMAT Developer Replenisher, Part A

Product code: 1249259 - Part A

Supplier: Carestream Health, Inc., 150 Verona Street, Rochester, New York, 14608

For Emergency Health Information call, (800) 424-9300

For other information contact 800-328-2910.

Synonyms: PCD 6159

Product Use: photographic processing chemical
For industrial use only.

2. Hazards identification

CONTAINS: Hydroquinone (123-31-9), Diethylene glycol (111-46-6), Potassium sulphite (10117-38-1), Sodium sulphite (7757-83-7)

WARNING!

HARMFUL IF SWALLOWED

CAUSES EYE IRRITATION

CAN CAUSE KIDNEY DAMAGE AND CNS EFFECTS FOLLOWING INGESTION

NFPA Hazard Ratings: Health - 2, Flammability - 1, Instability - 0

NOTE: NFPA 704 (2007) hazard indexes involves data review and interpretation that may vary among companies. It is intended only for rapid, general identification of the magnitude of the potential hazards. To adequately address safe handling, ALL information in this MSDS must be considered.

3. Composition/information on ingredients

Weight %	Components (CAS-No.)
20 - 25	Potassium sulphite (10117-38-1)
5 - 10	Hydroquinone (123-31-9)
1 - 5	Diethylene glycol (111-46-6)
1 - 5	Sodium sulphite (7757-83-7)
1 - 5	Sodium carbonate (497-19-8)

4. First aid measures

Inhalation: If inhaled, move to fresh air. Get medical attention if symptoms occur.

Material Safety Data Sheet

Revision Date: 08/16/2007
Z17000000227/Version: 1.1
Print Date: 10/29/2008
Page: 2/8

Eyes: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Skin: Wash off with soap and water. Get medical attention if symptoms occur.

Ingestion: If swallowed, only induce vomiting as directed by medical personnel. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

5. Fire-fighting measures

Extinguishing Media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Fire or excessive heat may produce hazardous decomposition products.

Hazardous Combustion Products: Carbon oxides, sulphur oxides, (see also Hazardous Decomposition Products section).

Unusual Fire and Explosion Hazards: None.

6. Accidental release measures

Methods for cleaning up: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination.

7. Handling and storage

Personal precautions: Avoid breathing mist or vapour at concentrations greater than the exposure limits. Avoid contact with eyes, skin, and clothing. Use only with adequate ventilation. Wash thoroughly after handling.

Prevention of Fire and Explosion: Keep from contact with oxidizing materials.

Storage: Keep container tightly closed. Keep away from incompatible substances (see Incompatibility section.)

8. Exposure controls / personal protection

Occupational exposure controls

Chemical Name	Regulatory List	Value Type	Value
Hydroquinone	ACGIH	time weighted average	2 mg/m3
	OSHA Z1	Permissible exposure limit	2 mg/m3
Sulphur dioxide	ACGIH	time weighted average	2 ppm
	ACGIH	Short term exposure limit	5 ppm
	OSHA Z1	Permissible exposure limit	5 ppm 13 mg/m3

Ventilation: Good general ventilation should be used. Ventilation should be sufficient so that applicable occupational exposure limits are not exceeded. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory protection may be needed in special circumstances.

Material Safety Data Sheet

Revision Date: 08/16/2007
Z17000000227/Version: 1.1
Print Date: 10/29/2008
Page: 3/8

Respiratory protection: None should be needed. If engineering controls do not maintain airborne concentrations below recommended exposure limits, an approved respirator must be worn. A respirator should be worn if hazardous decomposition products are likely to be or have been released. Respirator type: Acid gas. If respirators are used, a program should be instituted to assure compliance with applicable federal, state, commonwealth, provincial, or local laws and regulations.

Eye protection: Wear safety glasses with side shields (or goggles).

Skin and body protection: For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn.

Recommended Decontamination Facilities: Safety shower, eye wash, washing facilities as appropriate to condition of use.

9. Physical and Chemical Properties

Physical form: liquid

Colour: clear light yellow

Odour: odourless

Specific gravity: 1.305

Vapour pressure (at 20.0 °C (68.0 °F)) : 24 mbar (18.0 mm Hg)

Vapour density: 0.6

Volatile fraction by weight: 60 - 65 %

Boiling point/range: > 100.0 °C (> 212.0 °F)

Water solubility: complete

pH: 11.4

Flash point: > 93.3 °C (> 200.0 °F) (Setaflash closed cup)

10. Stability and reactivity

Stability: Stable under normal conditions.

Incompatibility: Acids, Strong oxidizing agents. Contact with strong acids may liberate sulphur dioxide.

Hazardous decomposition products: sulphur oxides.

Hazardous Polymerization: Hazardous polymerization does not occur.

11. Toxicological information

Material Safety Data Sheet

Revision Date: 08/16/2007
Z17000000227/Version: 1.1
Print Date: 10/29/2008
Page: 4/8

Effects of Exposure

General advice: This mixture contains hydroquinone which is classified as a dermal sensitizer in some jurisdictions. A very similar mixture was negative in dermal sensitization studies with and without prior sensitization to hydroquinone. Based on the results of these studies, this mixture is not expected to present a dermal sensitization hazard to humans. The following information is based, in part, on an analogy to: PCD 6400 (a very similar material). The toxicological properties of this material have not been investigated.

Contains: Hydroquinone. There is insufficient evidence for classifying hydroquinone as a suspected carcinogenic or mutagenic substance in humans. No increases in cancer rates were observed in an epidemiology study which looked at mortality among more than 800 persons employed primarily in the manufacture of hydroquinone. Carcinogenicity studies in animals were inconclusive. Rats and mice were given hydroquinone by stomach tube or at high concentrations in the diet. Responses were not consistent across route of exposure, species or sex. The International Agency for Research on Cancer (IARC) has classified hydroquinone in Group 3, i.e., "not classifiable" as a carcinogen. Hydroquinone is generally negative in bacterial mutagenicity tests; there is evidence for the clastogenicity (chromosome breakage) of hydroquinone in vivo and in vitro. The relevance of chromosomal effects in test animals in predicting human risk is unclear.

Contains: Diethylene glycol. Can cause kidney damage and CNS effects following ingestion. Repeated oral exposure to high doses can cause liver damage.

Inhalation: Expected to be a low hazard for recommended handling. Some asthmatics or hypersensitive individuals may experience difficulty breathing if exposed to aerosols or decomposition products that are not anticipated during normal use.

Eyes: Causes eye irritation.

Skin: Expected to be a low hazard for recommended handling.

Ingestion: Harmful if swallowed. Some asthmatics or sulfite-sensitive individuals may experience wheezing, chest tightness, stomach upset, hives, faintness, weakness and diarrhea. Can cause kidney damage and CNS effects following ingestion.

Data for PCD 6400 (a very similar material):

Acute Toxicity Data:

- Oral LD50 (rat): > 2,000 mg/kg
- Skin irritation: none
- Skin Sensitization: negative

Data for Hydroquinone (CAS 123-31-9):

Acute Toxicity Data:

- Oral LD50 (rat): 400 mg/kg
- Oral LD50 (male rat): 400 mg/kg
- Oral LD50 (male mouse): 100 - 200 mg/kg
- Dermal LD50 (guinea pig): > 1,000 mg/kg
- Dermal absorption rate: 1.1 micrograms (s) / cm² / hour

Material Safety Data Sheet

Revision Date: 08/16/2007
Z17000000227/Version: 1.1
Print Date: 10/29/2008
Page: 5/8

- Skin irritation: slight
- Skin Sensitization (guinea pig): positive
- Eye irritation: moderate

Mutagenicity/Genotoxicity Data:

- Salmonella typhimurium assay (Ames test): negative (in presence and absence of activation)
- Chromosomal aberration assay: negative (in absence of activation)
- Chromosomal aberration assay: positive (in presence of activation)
- Sister chromatid exchange (SCE) assay: positive (in presence and absence of activation)

Definitions for the following section(s): LOEL =lowest-observed-effect level, LOAEL = lowest-observed-adverse-effect, NOAEL = no observed-adverse-effect level, NOEL =no-observed-effect level.

Repeated dose toxicity:

- Dermal (17-day, rat): NOEL; 3800 mg/kg/day
- Dermal (17-day): LOEL (Lowest observable effect level); 4800 mg/kg/day

Developmental Toxicity Data:

- Oral (female rabbit): NOEL for developmental toxicity; 25mg/kg/day

Data for Potassium sulphite (CAS 10117-38-1):

Acute Toxicity Data:

- Oral LD50 (rat): > 3,200 mg/kg
- Oral LD50 (mouse): > 3,200 mg/kg
- Dermal LD50 (guinea pig): > 20,000 mg/kg
- Skin irritation: slight to moderate

Data for Diethylene glycol (CAS 111-46-6):

Acute Toxicity Data:

- Oral LD50 (rat): > 3,200 mg/kg
- Dermal LD50: > 10,000 mg/kg
- Skin irritation: slight to moderate
- Skin irritation: slight
- Eye irritation: slight

Data for Sodium carbonate (CAS 497-19-8):

Acute Toxicity Data:

- Oral LD50 (rat): 4,090 mg/kg
- Oral LD50 (rat): 1,600 - 3,200 mg/kg
- Skin irritation: slight

Data for Sodium sulphite (CAS 7757-83-7):

Acute Toxicity Data:

Material Safety Data Sheet

Revision Date: 08/16/2007
Z17000000227/Version: 1.1
Print Date: 10/29/2008
Page: 6/8

- Oral LD50 (rat): > 1,600 mg/kg
- Skin irritation: none
- Eye irritation: slight; washing palliative

12. Ecological information

The following properties are ESTIMATED from the components of the preparations.

Potential Toxicity:

Toxicity to fish (LC50):	< 1 mg/l
Toxicity to daphnia (EC50):	< 1 mg/l
Toxicity to algae (IC50):	1 - 10 mg/l
Toxicity to other organisms (EC50):	10 - 100 mg/l

Persistence and degradability: Readily biodegradable

Chemical Oxygen Demand (COD): 330 g/l

Biochemical Oxygen Demand (BOD): 114 g/l

13. Disposal considerations

Discharge, treatment, or disposal may be subject to federal, state, commonwealth, provincial, or local laws. Since emptied containers retain product residue, follow label warnings even after container is emptied.

14. Transport information

Not regulated for all modes of transportation.

For more transportation information, go to: <http://ship.carestreamhealth.com>.

15. Regulatory information

Notification status

Regulatory List	Notification status	Other information	Not listed
EINECS	n (Negative listing)	-	Calcium lignosulphonate
TSCA	y (positive listing)	On TSCA Inventory	
AICS	y (positive listing)	-	
DSL	y (positive listing)	All components of this product are on the Canadian DSL list.	
ENCS (JP)	y (positive listing)	-	

Material Safety Data Sheet

Revision Date: 08/16/2007
Z1700000227/Version: 1.1
Print Date: 10/29/2008
Page: 7/8

KECI (KR)	y (positive listing)	-
PICCS (PH)	y (positive listing)	-
INV (CN)	y (positive listing)	-

A N (Negative listing) indicates one or more component is either not on the public Inventory or is subject to exemption requirements. If additional information is needed contact Kodak.

Other regulations

American Conference of Governmental Industrial Hygienists (ACGIH):	Hydroquinone: Group A3 (Confirmed animal carcinogen with unknown relevance to humans.)
International Agency for Research on Cancer (IARC):	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
U.S. National Toxicology Program (NTP):	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
U.S. Occupational Safety and Health Administration (OSHA):	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
U.S. California Prop. 65:	none
US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required:	Hydroquinone
US. Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000):	No components are subject to Massachusetts Right To Know Act.
US. Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323):	Water, Potassium sulphite, Hydroquinone, Diethylene glycol
US. New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5):	Water, Potassium sulphite, Hydroquinone, Diethylene glycol, Sodium carbonate
US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR355, Appendix A):	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

16. Other information

The data below reflects current legislative requirements whereas the product in your possession may carry a different version of the label depending on the date of manufacture.

US/Canadian Label Statements:

CONTAINS: Hydroquinone (123-31-9), Diethylene glycol (111-46-6), Potassium sulphite (10117-38-1), Sodium sulphite (7757-83-7)

Material Safety Data Sheet

Revision Date: 08/16/2007
Z17000000227/Version: 1.1
Print Date: 10/29/2008
Page: 8/8

WARNING!
HARMFUL IF SWALLOWED
CAUSES EYE IRRITATION
CAN CAUSE KIDNEY DAMAGE AND CNS EFFECTS FOLLOWING INGESTION

Avoid prolonged or repeated breathing of mist or vapour.
Avoid contact with eyes, skin, and clothing.
Use only with adequate ventilation.
Wash thoroughly after handling.

FIRST AID: If inhaled, move to fresh air. Get medical attention if symptoms occur. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Wash contaminated clothing before re-use. Destroy or thoroughly clean contaminated shoes. If swallowed, only induce vomiting as directed by medical personnel. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Keep out of reach of children.

Do not handle or use until safety precautions in Material Safety Data Sheet (MSDS) have been read and understood.

Since emptied containers retain product residue, follow label warnings even after container is emptied.

IN CASE OF FIRE: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

IN CASE OF SPILL: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination.

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment. The information relating to the working solution is for guidance purposes only, and is based on correct mixing and use of the product according to instructions.

R-1, S-2, F-1, C-0